



**Características**  
 Characteristics  
 Caractéristiques



z  
 300 x 150 cm.  
 y  
 x



+ 3 años  
 100 cm.



Nº 1 u.  
 32,50 m<sup>2</sup>

<b>* Zona de salto</b> <i>Jumping zone</i> <i>Zone de saut</i>	2000 x 940 mm
<b>* Espacio libre (largo x ancho)</b> <i>Free space (length x width)</i> <i>Espace libre (longueur x largeur)</i>	6500 x 5000 mm
<b>* Bastidor</b> <i>Frame</i> <i>Châssis</i>	Acero galvanizado en caliente y sendzimir <i>Hot-dip and sendzimir galvanized steel</i> <i>Acier galvanisé à chaud et sendzimir</i>
<b>* Borde de seguridad</b> <i>Safety border</i> <i>Bordure de sécurité</i>	Loseta amortiguadora de caucho SBR/EPDM <i>Impact protection slab of SBR/EPDM rubber</i> <i>Dalle amortissante de caoutchouc SBR/EPDM</i>
<b>* Superficie de salto</b> <i>Jumping surface</i> <i>Superficie de saut</i>	Lamas móviles sintéticas <i>Synthetic moveable slats</i> <i>Lamelles mobiles synthétiques</i>